

Fujitsu Plasmavision Monitors 2007 Business Display Specification Comparison Chart



Display Type	Screen Size	Dimensions	Weight	Pixel Count	Contrast Ratio	Aspect Ratio	Displayable Colors	Computer Inputs	Viewing Angle	Horizontal kHz	Vertical Hz	Power Source	External Control	Operating Temperature	Relative Humidity	EMC Regulations	Safety Regulations	Warranty	MSRP	Optional Accessories	Optional Video Card		
P42VCA51WH	36.3" W x 20.4" H (42" diagonal)	40.7" W x 25.2" H x 3.3" D*	68.3 lbs	852 x 480 rectangular	10,000:1	16:9	1.07 billion colors	RGB 15-pin x 1	160 degrees	15.62 - 80.00	50.0 - 120.0	110 - 240 V, AC 50/60 Hz	RS-232C	32°F to 104°F	20 to 80 percent (not condensing)	FCC part-15 Class A, ICES-003 Class A, AS/NZS3548 Class A, EN55022 Class A	UL 6500, EN60065, IEC60065, U-CL	One year warranty on parts, labor and plasma display element	\$1,499	Desktop Stand Wall Mount Bracket Ceiling Bracket Matching Speakers (pair)	Desktop Stand Wall Mount Bracket P-50XP1-B P-CT4200-B P-42SP11-H	Desktop Stand Wall Mount Bracket P-50XP1-B P-CT4200-B P-42SP11-H	Desktop Stand Wall Mount Bracket P-50XP1-B P-CT4200-B P-50SP01-H
P42HCA51WH	36.3" W x 20.6" H (42" diagonal)	40.7" W x 25.2" H x 3.3" D*	65 lbs	1024 x 1024 rectangular	3,000:1	16:9	1.07 billion colors	RGB 15-pin x 1	160 degrees	15.62 - 80.00	50.0 - 120.0	110 - 240 V, AC 50/60 Hz	RS-232C	32°F to 104°F	20 to 80 percent (not condensing)	FCC part-15 Class A, ICES-003 Class A, AS/NZS3548 Class A, EN55022 Class A	UL 6500, EN60065, IEC60065, U-CL	One year warranty on parts, labor and plasma display element	\$3,999	Desktop Stand Wall Mount Bracket P-50XP1-B P-CT4200-B P-42SP11-H	Desktop Stand Wall Mount Bracket P-50XP1-B P-CT4200-B P-42SP11-H	Desktop Stand Wall Mount Bracket P-50XP1-B P-CT4200-B P-50SP01-H	Desktop Stand Wall Mount Bracket P-50XP1-B P-CT4200-B P-50SP01-H
P50XCA60WH	43.5" W x 24.5" H (50" diagonal)	47.7" W x 28.6" H x 3.9" D*	99.2 lbs	1366 x 768 rectangular	3,000:1	16:9	1.07 billion colors	RGB 15-pin x 1	160 degrees	15.62 - 80.00	50.0 - 120.0	110 - 240 V, AC 50/60 Hz	RS-232C	32°F to 104°F	20 to 80 percent (not condensing)	FCC part-15 Class A, ICES-003 Class A, AS/NZS3548 Class A, EN55022 Class A	UL 6500, EN60065, IEC60065, U-CL	One year warranty on parts, labor and plasma display element	\$5,499	Desktop Stand Wall Mount Bracket P-50XP1-B P-CT4200-B P-50SP01-H	Desktop Stand Wall Mount Bracket P-50XP1-B P-CT4200-B P-42SP11-H	Desktop Stand Wall Mount Bracket P-50XP1-B P-CT4200-B P-50SP01-H	Desktop Stand Wall Mount Bracket P-50XP1-B P-CT4200-B P-50SP01-H

* This is the depth of the main set cabinet. A small input housing adds 0.5", which does not affect mounting depth when using the recommended Fujitsu brand accessory wall bracket. Specifications are subject to change without notice for further improvement.

